



Series 1600
Vinyl Sliding Patio Door
with Mini Blinds

Series 1600 Vinyl Sliding Patio Door

FEATURES

- 4-7/8" Frame depth
- Integral nailing fin & J-channel
- 1" Insulated glass
- Double strength tempered glass
- Adjustable steel tandem rollers
- Double layered weatherstripping
- Fibermesh locking screen
- Two-lite door (OX, XO)
- Three-lite door (OXO, XOO, OOX)
- Four-lite door (OXXO)



OPTIONAL SELECTION

- Mini Blinds
- Low-E coating & argon filled IGU
- Custom finishes and custom colors
- GBG or exterior applied grids
- Keyed locked cylinder
- Field reversible
- Other optional Accessories

U-Factor: 0.21-0.46 SHGC: 0.17-0.61 VT: 0.31-0.66 Air Filtration (CFM/FT²): <0.30

Specification	XO	XO	OXO	OXO	OXXO
Test Size (W x H)	72" x 80"	96" x 96"	108" x 96"	108" x 80"	143" x 80"
AAMA Rating	LC-PG50	LC-PG35	LC-PG35	LC-PG50	R-PG30
Design Pressure (PSF)	50	35	35	50	40
Water Resistance (PSF)	7.52	7.52	7.52	7.52	4.60

Locations:

Queens, NYC HQ
Chicago, IL
St. Louis, MO
Dallas, TX
Scranton, PA
Cleveland, OH
Riverside, CA
Toronto, ON

31-10 Whitestone Expy, Flushing NY 11354
1300 W 35th St., Chicago IL 60609
300 Axminster Dr, Fenton MO 63026
454 W Mockingbird Ln, Dallas TX 75247
204 Franklin Valley Rd, Dalton PA 18414
29299 Clemens Rd, Suite 1B, Westlake Ohio 44145
1850 Atlanta Ave, Riverside CA 92507
30 West Pearce St., Richmond Hill ON L4B 1E3

(718) 961-7300
(773) 376-6688
(636) 305-7880
(469) 248-3012
(570) 276-8000
(440) 871-8694
(951) 779-9300
(905) 889-9883

www.crystalwindows.com



Crystal
WINDOW & DOOR
Crafted with Passion. Built to Perform.™



Manufacturer reserves the right to change product designs, specifications, details and pricing at any time without prior notification.